

Product Data Sheet

Colourcrete Form Oil

| | | | | | | | |
|---------------------------------------|--|---------|--------------|----------|---|------------|--------------------|
| Uses | Colourcrete Form oil is primarily used as a general-purpose release agent on construction sites. It is ideal for application to a wide range of surfaces such as timber, steel or fibreglass | | | | | | |
| Features | Effective on both steel and timber moulds Easy to apply through conventional spray equipment Highly stable during placement and vibration of concrete | | | | | | |
| Advantages | Allows for fast and easy striking of formwork Very economical Does not stain or contaminate the finished concrete Regular use will help to reduce the incidence of rust on steel moulds | | | | | | |
| Product Description | Oily blue liquid Diesel odour | | | | | | |
| Packaging | 5litre, 20litre or 210litre | | | | | | |
| Application | Colourcrete form Oil is supplied ready to use and should not be diluted Surfaces coated should be clean and free from grease, dirt or old concrete The optimum method of application is by conventional spray equipment; however, a brush or roller can also be used. Colourcrete Form Oil should be applied at the stated coverage rates to obtain a thin and even film over the entire surface of the mould or formwork. Any excess liquid remaining on the surface after application should be mopped of. Allow 1-3 hours to dry before pouring concrete. | | | | | | |
| Technical Data | <table style="width: 100%; border: none;"> <tr> <td style="width: 60%;">Density</td> <td>0.85kg/litre</td> </tr> <tr> <td>Coverage</td> <td>Timber up to 19m²/litre Steel up to 30m²/litre</td> </tr> <tr> <td>Shelf Life</td> <td>12 months from DOM</td> </tr> </table> | Density | 0.85kg/litre | Coverage | Timber up to 19m ² /litre Steel up to 30m ² /litre | Shelf Life | 12 months from DOM |
| Density | 0.85kg/litre | | | | | | |
| Coverage | Timber up to 19m ² /litre Steel up to 30m ² /litre | | | | | | |
| Shelf Life | 12 months from DOM | | | | | | |
| Clean up | N/A | | | | | | |
| Storage | Store in unopened original containers in dry conditions between +5°C and +30°C. Keep containers closed and in a well-ventilated area when not in use. Do not expose to direct sunlight in storage. | | | | | | |
| Additional Compatible products | | | | | | | |
| Health & Safety | For information and advice on the safe handling, storage and | | | | | | |

| | |
|------------------------|--|
| Information | disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet containing physical, ecological, toxicological and other safety-related data. |
| Limitations | Treated formwork should not be left exposed to heavy weathering or dust accumulation for long periods, maximum 7 days depending on conditions. New, unsealed timber will initially require 1-3 coats of Colourcrete Form Oil due to porosity of the timber. Only a thin film of the product is required to ensure maximum performance. Excess application may cause staining. |
| Contact Details | 0800 727 333 |
| Office Hours | Monday to Friday 7:30am – 4:30pm |
| Legal Notes | The information, and, in particular, the recommendations relating to the application and end-use of our products, are given in good faith based on our current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with our recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. We reserve the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request. It may be necessary to adapt the above disclaimer to specific local laws and regulations. |