

VIBRATING SCREED TORNADO E-BATT



The Tornado vibrating screed is an exceptional option when choosing to vibrate concrete. ENAR guarantees an optimum level of concrete compaction regardless of the type of concrete being vibrated. The profiles used on the Tornado are resistant and glide comfortably across concrete due to its flotability.

DESIGNED & MANUFACTURED IN EUROPE FOR QUALITY AND EFFICIENCY

Robust, easy to use and ergonomic are the most frequently used words when describing the Tornado from ENAR. The rubber handles conform to many regulations and also provide a reduced level of vibrations to the user. The range includes either petrol or electric motors.



+ Comfortable to Manage Reliably simple.

The Tornado from ENAR has handles that are designed to reduce the vibrations to the users' hands making it more comfortable when being used.

+ Light And easy to use.

This product can be easily used by one person on a job site thanks to its size and weight. This also allows for a better transportation of the product.



+ Safe & reliable No risk of electric shocks.

Its safety voltage of only 24V ensures the user's protection. The absence of cables eliminates the risk of electric shocks. It's failsafe automatically turns the machine off to prevent electric shocks to the user.



+ Zero Maintenance No spare parts, no waste generated.

Thanks to the Tornado's electronic conversion system, there are no parts that need to be replaced unlike the standard mechanical vibrators.



+ Eco-Friendly Ecological and zero emissions

Less environmental impact thanks to its battery-powered electric motor.

TECHNICAL DATA

MODEL	ENGINE	POWER (W)	FREQUENCY (vib/min)	CENTRIFUGAL FORCE (N)	WEIGHT (Kg)
TORNADO E-BATT	External vibrator 24V	130	5,500	1,400	12



Options

Extra Battery for Tornado E-BATT
VAS anti-vibration grips

BATTERY TECHNICAL DATA

VOLTAGE (V)	RATED CAPACITY (Ah)	AUTONOMY DURATION	LOADING TIME
24	14.5	✓ More than 2h.	± 3 h.

PROFILES

LENGTH (m)	WEIGHT (Kg)
1.5	4.6
2	6.2
2.5	7.8
3	9.3
4	12.5

- › High resistance, aluminium profiles.
- › Rounded ends to the profiles.
- › Strict flatness control while in use.
- › Profile base of 200mm/20cm to obtain a greater control and glide.
- › Profiles available from 1.5m to 4m .

